

# **Safety Data Sheet**

# prepared to UN GHS Revision 3

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier T-S301 Revision Date: 28/05/2021

Product Name: Alumanation 301

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Monocomponent industrial coating - Industrial use.

Supersedes Date:

**New SDS** 

1.3 Details of the supplier of the safety data sheet

Importer: Importer

Manufacturer: StonCor Africa (Pty.) Ltd.

8 Cresset Road

Midrand Industrial Park, Chloorkop

P.O. Box 2205 2001, Johannesburg

South Africa

Regulatory / Technical Information:

+27 11 254 5500

Datasheet Produced by: Chonco, Cebolonkosi - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside US)

Giftinformasjonen: +47 22 59 13 00

# 2. Hazard Identification

# 2.1 Classification of the substance or mixture

Carcinogenicity, category 1A Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1A

#### 2.2 Label elements

# Symbol(s) of Product





# Signal Word

Danger

#### Named Chemicals on Label

quartz (silicon dioxide)

#### **HAZARD STATEMENTS**

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Germ Cell Mutagenicity, category 1A	H340-1A	May cause genetic defects.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P284	Wear respiratory protection.
	P308+313	IF exposed or concerned: Get medical advice/attention.

closed.

Store in a well-ventilated place. Keep container tightly

# 2.3 Other hazards

No Information

# Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

P403+233

# 3. Composition/Information On Ingredients

#### 3.2 **Mixtures** Hazardous ingredients <u>%</u> Name According to EEC **EINEC No.** CAS-No. Classifications Aluminium powder 231-072-3 7429-90-5 10 - <25 H261 (pyrophoric) Solvent naphtha 265-198-5 64742-94-5 10 - <25 H304 (petroleum), heavy arom. Solvent naphtha 265-191-7 64742-88-7 10 - <25 H304 (petroleum), medium äliph. Solvent naphtha 265-200-4 64742-96-7 2.5 - < 10 (petroleum), heavy aliph. Stoddard solvent 232-489-3 8052-41-3 2.5 - < 10 H226-304-340-350 93763-70-3 618-970-4 2.5 - < 10 expanded perlite 9004-34-6 232-674-9 1.0 - < 2.5 cellulose

Solvent naphtha (petroleum), light arom.	265-199-0	64742-95-6	1.0 - <2.5	H304-411
quartz (silicon dioxide)	238-878-4	14808-60-7	0.1 - <1.0	H350-370

CAS-No.	M-Factors
7429-90-5	0
64742-94-5	0
64742-88-7	0
64742-96-7	0
8052-41-3	0
93763-70-3	0
9004-34-6	0
64742-95-6	0
14808-60-7	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

# 4. First-aid Measures

# 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

# Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

# 4.2 Most important symptoms and effects, both acute and delayed

No Information

# 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

# 5.2 Special hazards arising from the substance or mixture

No Information

# 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

# 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

# 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# 7. Handling and Storage

# 7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
Aluminium powder (pyrophoric)	7429-90-5				
Solvent naphtha (petroleum), heavy arom.	64742-94-5				
Solvent naphtha (petroleum), medium aliph.	64742-88-7				
Solvent naphtha (petroleum), heavy aliph.	64742-96-7				
Stoddard solvent	8052-41-3				
expanded perlite	93763-70-3				
cellulose	9004-34-6				
Solvent naphtha (petroleum), light arc	om. 64742-95-6				
quartz (silicon dioxide)	14808-60-7				
Nama	CAS No	OEL Note			
<u>Name</u>	<u>CAS-No.</u>	OEL Note			
Aluminium powder (pyrophoric)	7429-90-5				
Solvent naphtha (petroleum), heavy arom.	64742-94-5				

Solvent naphtha (petroleum), medium 64742-88-7

aliph.

Solvent naphtha (petroleum), heavy 64742-96-7

aliph.

Stoddard solvent 8052-41-3

expanded perlite 93763-70-3

cellulose 9004-34-6

Solvent naphtha (petroleum), light arom. 64742-95-6

quartz (silicon dioxide) 14808-60-7

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

## 8.2 Exposure controls

**Personal Protection** 

**RESPIRATORY PROTECTION:** Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

**HAND PROTECTION:** Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

areas.

# 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Viscous Silver Grey Liquid

Physical State Liquid
Odor Solvent

Odor thresholdNot determinedpHNot determined

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) 80 - 154

Flash Point, (°C) 35

Evaporation rate Slower than ether

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

limits

0.6 - 7

Vapour Pressure Not determined
Vapour density Heavier than air

Relative density 1.01 - 1.06
Solubility in / Miscibility with water Insoluble

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C) Not determined

Viscosity 100 - 120 KU
Explosive properties Not determined

Oxidising properties

Not determined

#### 9.2 Other information

VOC Content g/l: Calculated grams of VOC per liter of coating product as applied. Specific Gravity (g/cm3) 1.020

# 10. Stability and Reactivity

#### Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Direct sources of heat.

# 10.5 Incompatible materials

Strong oxidizing agents.

# 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

# Information on toxicological effects

STOT-repeated exposure:

**Acute Toxicity:** 

Oral LD50: No information available. Inhalation LC50: No information available.

No information available. Irritation:

Corrosivity: No information available.

Sensitization: No information available.

No information available. Repeated dose toxicity:

Carcinogenicity: No information available.

Mutagenicity: No information available.

No information available. **Toxicity for reproduction:** 

No information available. STOT-single exposure: No information available.

No information available. Aspiration hazard:

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
64742-88-7	Solvent naphtha (petroleum), medium aliph.	>2000 mg/kg, oral. rat			0.000	0.000

Solvent naphtha (petroleum), 0.000 0.000 64742-96-7 20000 mg/kg heavy aliph. 3670 ppm/8 4700 mg/kg, Solvent naphtha (petroleum), 64742-95-6 >2000 ma/ka hours, rat, 0.000 0.000 light arom. oral, rat inhalation

#### **Additional Information:**

This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

# 12. Ecological Information

#### 12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
7429-90-5	Aluminium powder (pyrophoric)	No information	No information	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	No information	No information	
64742-88-7	Solvent naphtha (petroleum), medium aliph.	No information	No information	
64742-96-7	Solvent naphtha (petroleum), heavy aliph.	No information	No information	No information
8052-41-3	Stoddard solvent	No information	No information	
93763-70-3	expanded perlite	No information	No information	
9004-34-6	cellulose	No information	No information	
64742-95-6	Solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
14808-60-7	quartz (silicon dioxide)	No information	No information	

# 13. Disposal Considerations

<sup>13.1</sup> WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

14.1 UN number Not applicable

**14.2** UN proper shipping name Not regulated for transport according to U.S. DOT, ADR/RID, IMDG,

and IATA regulations.

Technical name

Not applicable

14.3 Transport hazard class(es)

Subsidiary shipping hazard

Not applicable

Not applicable

14.4 Packing group

Not applicable

Not applicable

Not applicable

14.5 Environmental hazards Not applicable
14.6 Special precautions for user Not applicable
EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

## **National Regulations:**

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

WGK Class: Not available

# 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour.

H261 In contact with water releases flammable gas. H304 May be fatal if swallowed and enters airways.

H340 May cause genetic defects.

H350 May cause cancer.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

#### Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.